
Posted by [DarkMaster](#) on Fri, 20 Feb 2026 12:38:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
select 'DOMAIN' AS OBJECT_TYPE,rdb$fields.rdb$field_name AS NAME
from rdb$fields
where rdb$fields.RDB$SYSTEM_FLAG=0 and not(rdb$fields.RDB$FIELD_NAME starting with
'RDB$') and
(
  (rdb$fields.RDB$DEFAULT_SOURCE containing 'CURRENT_TIME') or
  (rdb$fields.RDB$DEFAULT_SOURCE containing 'CURRENT_TIMESTAMP')
)

union
select 'TRIGGER' AS OBJECT_TYPE,

      iif(coalesce(rdb$triggers.rdb$relation_name,"")=","trim(coalesce(rdb$triggers.rdb$relation_name,""))||'.')||rdb$triggers.rdb$trigger_name AS NAME
from rdb$triggers
where rdb$triggers.rdb$system_flag=0 and not(rdb$triggers.rdb$trigger_name starting with
'RDB$') and
(
  (rdb$triggers.rdb$trigger_source containing 'CURRENT_TIME') or
  (rdb$triggers.rdb$trigger_source containing 'CURRENT_TIMESTAMP')
)

union
select 'PROCEDURE' AS OBJECT_TYPE,rdb$procedures.rdb$procedure_name AS NAME
from rdb$procedures
where rdb$procedures.rdb$system_flag=0 and not(rdb$procedures.rdb$procedure_name starting
with 'RDB$') and
(
  (rdb$procedures.rdb$procedure_source containing 'CURRENT_TIME') or
  (rdb$procedures.rdb$procedure_source containing 'CURRENT_TIMESTAMP')
)
```

```
union
select 'PROCEDURE PARAMS' AS
OBJECT_TYPE,rdb$procedure_parameters.rdb$procedure_name||'.'||rdb$procedure_parameters.
rdb$parameter_name AS NAME
from rdb$procedure_parameters
where (
    (rdb$procedure_parameters.rdb$default_source containing 'CURRENT_TIME') or
    (rdb$procedure_parameters.rdb$default_source containing
'CURRENT_TIMESTAMP')
)
```

```
union
select 'TABLE FIELDS' AS OBJECT_TYPE,
    trim(rdb$relation_fields.rdb$relation_name)||'.'||rdb$relation_fields.rdb$field_name
AS NAME
from rdb$relation_fields
where not(rdb$relation_fields.rdb$relation_name starting with 'RDB$') and
    (
    (rdb$relation_fields.rdb$default_source containing 'CURRENT_TIME') or
    (rdb$relation_fields.rdb$default_source containing 'CURRENT_TIMESTAMP')
)
```

-> LOCALTIMESTAMP.